



The JOLLY-FLEX system is a modular design conveyor that can be used in any industrial application



Thanks to its aluminum structure with flat sides, is specially fit for food and packaging industry, where is mandatory to minimize any sedimentation problem.

The JOLLY-FLEX system can use different types of chain: full plastic chain or metal chain with plastic slats that allow high workloads.

Standard sizes of chain width available are:

- 83 mm (3.25 inches)
- 114 mm (4.50 inches)
- 191 mm (7.50 inches)
- 254 mm (10.00 inches)
- 305 mm (12.00 inches)

Straight and bended tracks are available to meet any possible layout requirement.

EXAMPLES OF APPLICATIONS



BOX OF MEDIUM TO BIG SIZE



TRAYS



HEAVY BAGS



SOFT, PLASTIC ENVELOPES



Complete line of Jolly-Flex conveyors for handling of bakery products



Multiple lines of Jolly-Flex for sweets packaging line





TECH SUMMARY *

product size:	30 mm - 600 mm
product weight:	50 kg for horizontal transport, 20 kg for vertical transport
maximum weight on the conveyor:	200 kg - 400 kg
maximum conveyor length:	30 m - 40 m
maximum speed of transport:	60 m/min - 70 m/min



*Please note that these data are rule of thumb. Data may change depending on product weight, track length, number of bends, speeds, motor size and chain type. Please contact our engineering department for further request.